

MULTIFIRE 45 IDRO FLAT DOOR

Versatile system with automatic feed and wood or pellet combustion, it operates like a real boiler. Cast iron firebox featuring Palazzetti's dual combustion system, with pellet box. Automatic ignition, programmable, with standard supplied rotating self-cleaning brazier and "star" pellet-feed system.

TECHNICAL SPECIFICATIONS

Dimensions	82 x 55 x 177 cm - Weight: 220 kg
Exhaust outlet fitting	ø cm 15
Air Intake	14 cm
When burning wood:	
Nominal heat input	18.36 (Kw) - 15800 (Kcal/h)
Nominal heat output	14.3 (Kw) - 12300 (Kcal/h)
Nominal heat output to water	6.9 (Kw) - 6000 (Kcal/h)
Efficiency at nominal heat output	77.9 %
Hourly fuel consumption	4.1 (kg/h)
When burning pellet:	
Nominal heat input	17.28 (Kw) - 14900 (Kcal/h)
Efficiency at nominal heat output	84.5 %
Efficiency at reduced heat output	86.9 %
Nominal heat output	14.6 (Kw) - 12600 (Kcal/h)
Nominal heat output to water	8.95 (Kw) - 7700 (Kcal/h)

Reduced heat output	5.01 (Kw) - 4400 (Kcal/h)
Reduced heat output to water	3.12 (Kw) - 2700 (Kcal/h)
Fuel hopper capacity	22 (kg)
Hourly fuel consumption	1.2 (kg/h) - 3.7 (kg/h)

STANDARD EQUIPMENT



VERSION

MULTIFIRE 45 IDRO FLAT DOOR - TOP VERSION

ACCESSORIES

GSM CONTROL (A)

PELLET SENSOR

DOWNLOAD

● INSTRUCTIONS FOR USE AND MAINTENANCE